
The `unicedefonttable` package*

Frank Mittelbach

Abstract

A package for typesetting font tables for larger fonts, e.g., TrueType or OpenType Unicode fonts. To produce a one-off table, a standalone version is available as well.

Contents

1	Introduction	287
2	The user interface	288
2.1	Keys and their values	289
2.2	A standalone interactive version	291
3	Notes on the table data	291
A	Index	292
B	Examples	292
B.1	Computer Modern Sans — 7-bit font	292
B.2	T _E X Gyre Heros — 8-bit font	293
B.3	Latin Modern Math — 8-bit fonts	293
B.4	Latin Modern Math compared to New Computer Modern Math . .	295
B.5	Garamond Libre's Byzantine Musical Symbols	303

1 Introduction

When I started to write a new chapter for the third edition of *The L^AT_EX Companion* on modern fonts available for different L^AT_EX engines, I was a bit surprised that I couldn't find a way to easily typeset tables showing the glyphs available in TrueType or OpenType fonts. The `nfssfont` package available with L^AT_EX only supports fonts from the 8-bit world, but modern fonts that can be used with X_HT_EX or LuaT_EX can contain thousands of glyphs and having a method to display what is available in them was important for me.

I therefore set out to write my own little package and what started as an afternoon exercise ended up being this package, offering plenty of bells and whistles for typesetting such font tables.

As there can be many glyphs in such fonts a tabular representation of them might run for several pages, so the package internally uses the `longtable` package to handle that. In most cases the glyphs inside the fonts are indexed by their Unicode numbers so it is natural to display them sorted by their position in the Unicode character set.

Unicode is organized in named blocks such as “Basic Latin”, “Latin-1 Supplement”, etc., typically consisting of 265 characters each.¹ It is therefore helpful to use these block names as subtitles within the table, to more easily find the information one is looking for.

A common way to represent the number of a single Unicode character is U+ followed by four (or more) hexadecimal digits. For example, U+0041 represents the letter “A” and U+20AC the Euro currency symbol “€”. We use this convention by showing a Unicode range of sixteen characters at the left of each table row, e.g., U+0040 – 004F, followed by the sixteen glyphs in the range. Thus that particular table row from the “Basic

* This is version v1.0e of the package, dated 2021/10/29; the license is LPPL.

¹ Some blocks are smaller, while those containing the Asian ideographs are much larger.

Latin” block would show something like

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0040 – 004F	Ⓐ	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O

If a Unicode character has no glyph representation in a given font then this is indicated by a special symbol (by default a colored hyphen). By default some color is used, but we’ve grayscaled the output for *TUGboat*.

In order to easily locate any Unicode character the table shows by default sixteen hex digits as a column heading. For example, to find Euro currency symbol (U+20AC) one first finds the right row, which is the range U+20A0 – 20AF, and then the C column in that row, and the glyph is there (or an indication that the font is missing that glyph; the line shows that for some of the other slots).

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+20A0 – 20AF	-	₡	-	-	£	-	₦	-	-	₩	-	đ	€	-	-	-

It can be useful to compare two fonts with each other by filling the table with glyphs from a secondary font if the primary font is missing them. For example, the next display shows two rows of Latin Modern Math (black glyphs) and instead of showing a missing glyph symbol in most slots, we use the glyphs from New Computer Modern Math, which has a much larger glyph set (normally red glyphs with gray background but again, grayscaled for *TUGboat*).

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+2A00 – 2A0F	⊕	⊕	⊗	∪	⊕	∏	⊸	ℳ	ℳ	ℳ	ℳ	ℳ	ℳ	ℳ	ℳ	ℳ
U+2A10 – 2A1F	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ

2 The user interface

The package offers one command to typeset a font table. The appearance of the table can be customized by specifying key/value pairs.

\displayfonttable

```
\displayfonttable * [<key/value-list>] {<font-name>} [<font-features>]
```

The *<font-name>* is the font to be displayed. This and the *<font-features>* argument are passed to `fontspec`, thus they should follow the conventions of that package for specifying a font. The *<key/value-list>* offers customization possibilities discussed below. The `\displayfonttable*` is a variant of the command, intended for use with 8-bit legacy fonts. It presets some keys, but otherwise behaves identically. The preset values are:

```
nostatistics, display-block=none, hex-digits=head, range-end=FF
```

For details see the next section.

\fonttablesetup

```
\fonttablesetup {<key/value-list>}
```

Instead of or in addition to specifying key/values to `\displayfonttable` it is possible to set them up as defaults. Inside `\displayfonttable` the defaults are applied first, so one can still overwrite their values for an individual table.

\fonttableglyphcount

```
\fonttableglyphcount
```

While typesetting a font table the package keeps track of the number of glyphs it finds in the font. After the table has finished, this value is available in `\fonttableglyphcount` and it is, for example, used when statistics are produced. At the start of the next table it is reset to zero.

2.1 Keys and their values

Several of the available keys are booleans accepting `true` or `false`. They usually exist in pairs so that one can specify the desired behavior without needing to provide a value, e.g., specifying `header` is equivalent to specifying `header=true` or `noheader=false`, etc. In the lists below the default settings are indicated by an underline.

`header`
`noheader`
`title-format`
`title-format-cont`

The first set of keys is concerned with the overall look and feel of the generated table.

header, noheader These keys determine whether a header to the table is produced.

title-format, title-format-cont These keys define what is provided as a header title or continuation title if the table consists of several pages. They expect code as their value. This code can contain #1 and #2 to denote the *<font-name>* and *<font-features>* arguments, respectively.

By default a title using the `\caption` command is produced; on continuation titles, the *<font-features>* are not shown. This is typeset as a `longtable` header row, so you either need to use `\multicolumn` or a `\caption` command—otherwise everything ends up in the first column.

`display-block`
`hex-digits`
`color`

These keys handle the inner parts of the table.

display-block The Unicode dataset is organized in named blocks that are typically 128 or 256 characters, though some are noticeably larger and a few are smaller. With the `display-block` key it is possible to specify if and how such blocks should be made visible. The following values are supported:

titles Above each display block that contains glyphs the Unicode title of the block is displayed.

rules Display blocks are indicated only by a `\midrule`.

none Display blocks are not indicated at all.

hex-digits To ease reading the table, rows of hex digits are added to it. Where or if this happens is controlled by this key. Allowed values for it are the following:

block A row of hex digits is placed at the beginning of each Unicode block containing glyphs in the displayed font.

foot A row is added to the foot of each table page.

head A row is added to the top of each table page.

head+foot A row is added to the top and the foot of each table page.

none All hex digit rows are suppressed.

hex-digits-font The font to use for the hex digits, by default `\ttfamily\scriptsize`.

color This key determines the color for parts of the table (hex digits and Unicode ranges). It can be either `none` or a color specification as understood by the `\color` command. The default is `blue`.

`statistics`
`nostatistics`
`statistics-font`
`statistics-format`

The next set of keys allows altering the statistics that are produced.

statistics, nostatistics These keys determine whether some statistics are listed at the end of the table.

statistics-font The font used to typeset the statistics; the default is `\normalfont\small`.

statistics-format Code (text) to specify what should be typeset in the statistics. One can use #1 for the *<font-name>* and #2 for the glyph count. The material is typeset on a single line at the end of the table. If several lines are needed you need to use `\parbox` or a similar construct.

glyph-width
missing-glyph
missing-glyph-font
missing-glyph-color

Another set of keys deals with customization on the glyph level.

glyph-width All glyphs are typeset in a box with the same width, the default value is 6pt which is suitable for most 10pt fonts and make the table fit comfortably into the text width of a typical document.

missing-glyph If a slot in a row doesn't have a glyph in the font you may still want display something to indicate this state. By giving the key a value any arbitrary glyph or material can be typeset. The default is to typeset a - (hyphen) in a special color.

Rows that contain no glyph whatsoever are not displayed at all. Instead a small vertical space is added to indicate the one or more rows are omitted.

missing-glyph-font The font used for the missing glyphs (the default value is \ttfamily\scriptsize).

missing-glyph-color If not specified it uses the value specified with the **color** key. If you want a different color, e.g., **red**, you can use a color value or you can specify **none** to use no coloring.

compare-with
compare-color
compare-bgcolor
statistics-compare-format

You can make comparisons between two fonts, which is useful, for example when dealing with incomplete math fonts and you need to see how well the symbols from one font blend with the supplementary symbols from another font.

compare-with If given, the value is a **(comparison-font-name)** that is used to supply missing glyphs. This means that if the **(font-name)** to be displayed is missing a glyph in a slot, then the **(comparison-font-name)** is checked, and if that font has the glyph in question, it will be displayed instead of showing a missing glyph indicator.

compare-color, **compare-bgcolor** To distinguish real glyphs from missing but substituted glyphs, they can be colored specially (default red) and/or you can have their background colored (default is black!10, i.e., a light gray).

statistics-compare-format Code (text) to specify what should be typeset in the statistics when comparing two fonts. One can use #1 for the **(font-name)** and #2 for its glyph count, #3 is the name of the comparison font, #4 its glyph count, #5 for the number of glyphs missing in this font and #6 the number of extra glyphs in it. This code is used instead of **statistics-format** when comparisons are made. The material is typeset on a single line at the end of the table. If several lines are needed you need to use **\parbox** or a similar construct.

range-start
range-end

Finally there are two keys for restricting the display range.

range-start, **range-end** The full Unicode set of characters is huge and checking every slot to see if the current font contains a glyph in the slot takes a long time. If you know that font contains only a certain subset then you can speed up the table generation considerably by limiting the search (and consequently the output generation). The **range-start** specifies where to start with the search (default 0000) and **range-end** gives the last slot that is tested (default FFFF).

Thus, by default we restrict the display to slots below 10000, because text fonts seldom contain glyphs in the higher planes. But if you want to see everything of the font (as far as supported by this package) and are prepared to wait for the higher planes to be scanned, you can go up to a value of FFFFF.

These keys are also quite useful in combination with the previous **compare-with** key, to display only, for example, the Greek letters and see how glyphs from two fonts blend with each other.

2.2 A standalone interactive version

If you want to quickly display a single font, you can run `unicodelfont.tex` through LuaTeX (or XeTeX). Similar to `nfssfont.tex` (which is for 8-bit fonts with pdfTeX) it asks you a few questions and then generates the font table for you. There are fewer configuration options available, but this workflow saves you writing a document to get a one-off table.

Most font tables need several runs due to the use of `longtable`, which has to find the right width for the columns across several pages. The `unicodelfont` file therefore remembers your selection from the previous run and asks you if you want to reapply it to speed up the process.

3 Notes on the table data

If you look at some parts of a Unicode font table you see a number of slots that do not show a “missing glyph” sign, but nonetheless appear to be empty. For example:

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0020 – 002F	!	”	#	\$	%	&	'	()	*	+	,	-	.	/	
U+0030 – 003F	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
U+0040 – 004F	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
U+0050 – 005F	P	Q	R	S	T	U	V	W	X	Y	Z	[\]	^	_
U+0060 – 006F	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
U+0070 – 007F	p	q	r	s	t	u	v	w	x	y	z	{		}	~	-
U+00A0 – 00AF	ı	€	£	¤	¥	₩	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪
U+00B0 – 00BF	°	±	²	³	'	μ	¶	.	,	¹	²	»	¼	½	¾	᳚

The reason is that Unicode contains a lot of special spaces or otherwise invisible characters, e.g., U+0020 is the normal space, U+00A0 is a non-breaking space, U+00AD is a soft-hyphen (what LATEX users would indicate with \text{‐}), and so forth. Especially the row U+2000–200F in Table 6 looks strange as it appears to be totally empty, but in fact most of its slots contain spaces of different width.

General Punctuation

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+2000 – 200F	–	—	—	—	—	—	—		=	‘	’	,	–	“	”	–
U+2010 – 201F	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐	‐
U+2020 – 202F	†	‡	•	‐	‐	‐	‐	...	‐	‐	‐	‐	‐	‐	‐	‐

Another somewhat surprising area is the “Mathematical Alphanumeric Symbols” block in math fonts, starting at U+1D400. There you see a number of missing characters, the first two being U+1D455 (math italic small h) and U+1D49D (math script B).

Mathematical Alphanumeric Symbols

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+1D400 – 1D40F	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
U+1D410 – 1D41F	Q	R	S	T	U	V	W	X	Y	Z	a	b	c	d	e	f
U+1D420 – 1D42F	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v
U+1D430 – 1D43F	w	x	y	z	A	B	C	D	E	F	G	H	I	J	K	L
U+1D440 – 1D44F	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	a	b
U+1D450 – 1D45F	c	d	e	f	g	‐	i	j	k	l	m	n	o	p	q	r
U+1D460 – 1D46F	s	t	u	v	w	x	y	z	A	B	C	D	E	F	G	H
U+1D470 – 1D47F	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X

U+1D480 – 1D48F	Y	Z	a	b	c	d	e	f	g	h	i	j	k	l	m	n
U+1D490 – 1D49F	o	p	q	r	s	t	u	v	w	x	y	z	Ā	-	Č	Đ
U+1D4A0 – 1D4AF	-	-	đ	-	-	đ	Ķ	-	-	Ņ	Ņ	Ŗ	Ŗ	-	Ŗ	Ŗ
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

In this case the reason is *not* that the font fails to implement the characters, but that these characters have already been defined in earlier revisions of the Unicode standard in the lower Unicode plane. For example, the “h” is the Planck constant U+210E and U+212C is the script capital B, etc. The Unicode Consortium decided not to encode the *same* character twice, hence the apparent holes.

A Index

Numbers written in italic refer to the page where the corresponding entry is described or mentioned.

\-	291	missing-glyph-color	290
\caption	289	missing-glyph-font	290
\color	289	\multicolumn	289
color	289	noheader	289
compare-bgcOLOR	290	\normalfont	289
compare-color	290	nostatistics	289
compare-with	290	\parbox	289, 290
display-block	289	range-end	290
\displayfonttable	288, 288, 292	range-start	290
\displayfonttable*	288	\scriptsize	289, 290
\fonttableglyphcount	288	\small	289
\fonttablesetup	288	statistics	289
glyph-width	290	statistics-compare-format	290
header	289	statistics-font	289
hex-digits	289	statistics-format	289
\midrule	289	title-format	289
missing-glyph	290	title-format-cont	289
		\ttfamily	289, 290

B Examples

In this section we show the results of a few calls to \displayfonttable. The tables are a bit easier to navigate if they use color in some places, but for *TUGboat* this is not practical, so we use black and gray.

B.1 Computer Modern Sans — 7-bit font

Our first example is the original Computer Modern Sans, with character codes ≤ 127 . Command used:

```
\displayfonttable*[color=none, range-end=7F]{cmss10}
```

Table 1: cmss10

0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	
U+0000 – 000F	Γ	Δ	Θ	Λ	Ξ	Π	Σ	Τ	Φ	Ψ	Ω	ff	fi	fl	ffi	ffl

Table 1: cmss10 *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0010-001F	I	J	`	,	~	~	-	°	,	ß	æ	œ	ø	Æ	Œ	Ø
U+0020-002F	-	!	"	#	\$	%	&	'	()	*	+	,	-	.	/
U+0030-003F	0	1	2	3	4	5	6	7	8	9	:	;	i	=	ı	?
U+0040-004F	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
U+0050-005F	P	Q	R	S	T	U	V	W	X	Y	Z	[“	”	^	.
U+0060-006F	‘	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
U+0070-007F	p	q	r	s	t	u	v	w	x	y	z	-	—	“	~	”

B.2 TEX Gyre Heros — 8-bit font

This example shows the TEX Gyre Heros 8-bit font, in the T1 encoding, with character codes ≤ 255 . Command used:

```
\displayfonttable*[color=none]{ec-qhvr}
```

Table 2: ec-qhvr

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0000-000F	`	,	^	~	..	~	°	~	-	.	š	ć	,	‘	’	>
U+0010-001F	“	”	„	„	„	„	—	—	„	„	í	ff	fi	fl	ffi	ffl
U+0020-002F	„	!	”	#	\$	%	&	,	()	*	+	,	-	.	/
U+0030-003F	0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
U+0040-004F	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
U+0050-005F	P	Q	R	S	T	U	V	W	X	Y	Z	[\]	^	-
U+0060-006F	‘	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
U+0070-007F	p	q	r	s	t	u	v	w	x	y	z	{	—	}	~	-
U+0080-008F	Ā	Ā	Ć	Ć	Đ	Ē	Ē	Ğ	Ĺ	Ĺ	܍	܍	܍	܍	܍	܍
U+0090-009F	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	Ŗ	܍	܍	܍	܍	܍	܍
U+00A0-00AF	ă	ă	ć	ć	đ	é	é	ğ	í	í	ł	ń	ń	ñ	õ	ŕ
U+00B0-00BF	ř	ř	ř	ř	ř	ř	ř	ř	ř	ř	ž	ž	ž	ž	ž	ž
U+00C0-00CF	À	Á	Â	Ã	Ä	Å	Æ	Ç	È	È	Ê	Ê	Ë	Í	Í	Í
U+00D0-00DF	Đ	Ñ	Ò	Ó	Ô	Õ	Ö	Œ	Ù	Ù	Û	Û	Ü	Ý	Þ	SS
U+00E0-00EF	à	á	â	ã	ä	å	æ	ç	è	é	ê	ë	ì	í	î	í
U+00F0-00FF	ð	ñ	ò	ó	ô	õ	ö	œ	ø	ù	ú	û	ü	ý	þ	þ

B.3 Latin Modern Math — 8-bit fonts

The traditional Latin Modern Math Italic, Symbol and Extension fonts. The symbol font (lmsy10) has two characters added to the Computer Modern symbol repertoire, seen in the last row of the table. Commands used:

```
\displayfonttable*[color=none]{lmmi10}
\displayfonttable*[color=none]{lmsy10}
\displayfonttable*[color=none]{lmex10}
```

Table 3: lmmi10

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0000-000F	Γ	Δ	Θ	Λ	Ξ	Π	Σ	Υ	Φ	Ψ	Ω	α	β	γ	δ	ϵ
U+0010-001F	ζ	η	θ	ι	κ	λ	μ	ν	ξ	π	ρ	σ	τ	v	ϕ	χ
U+0020-002F	ψ	ω	ε	ϑ	ϖ	ϱ	ς	φ	\leftrightharpoons	\leftrightharpoons	\rightarrowtail	\leftarrowtail	\circ	\triangleright	\triangleleft	
U+0030-003F	o	1	2	3	4	5	6	7	8	9	.	<	/	>	★	
U+0040-004F	∂	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O

Table 3: lmmi10 *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0050-005F	P	Q	R	S	T	U	V	W	X	Y	Z	þ	ȝ	#	ȝ	ȝ
U+0060-006F	ℓ	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o
U+0070-007F	p	q	r	s	t	u	v	w	x	y	z	ȝ	J	ȝ	ȝ	ȝ

Table 4: lmsy10

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+0000-000F	—	·	×	*	÷	◊	±	⊐	⊕	⊖	⊗	∅	○	○	●	
U+0010-001F	≈	≡	≤	≥	≤	≥	≤	≥	~	≈	⊂	⊃	≪	≫	~,	~,
U+0020-002F	←	→	↑	↓	↔	↗	↘	≈	≤	⇒	↑	↓	↔	↖	↙	∞
U+0030-003F	†	∞	∈	∃	△	▽	/	·	∀	∃	¬	∅	ℝ	ℚ	ℤ	⊥
U+0040-004F	ℵ	𝒜	ℬ	𝒞	𝒟	ℰ	𝒻	𝒢	𝒦	𝒢	𝒢	𝒢	𝒢	ℳ	ℳ	ℳ
U+0050-005F	𝒫	𝒬	𝒫	𝒮	𝒯	𝒰	𝒩	𝒲	𝒳	𝒬	𝒪	𝒰	∩	∪	∧	∨
U+0060-006F	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤	⊤
U+0070-007F	√	II	∇	ʃ	□	□	□	□	§	†	‡	♣	◊	♡	♠	
U+00A0-00AF	-	-	-	-	-	-	-	-	-	-	-	-	≤	≥	-	-

Table 5: lmex10

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	
U+0000-000F	()	[]	[]	[]	{	}	<	>			/	\	
U+0010-001F	()	()	[]	[]	[]	{	}	<	>	/	\	
U+0020-002F	()	[]	[]	[]	{	}	<	>	/	\	/	\	
U+0030-003F	()	[]	[]					{	}					
U+0040-004F	()			<	>	□	□	§	ƒ	∫	⊕	⊕	⊕	⊗	⊗	
U+0050-005F	Σ	Π	∫	∪	∩	⊕	Λ	∨	Σ	Π	∫	∪	∩	⊕	Λ	∨	
U+0060-006F	Π	Π	^	—	—	~	~	~	~	~	[]	[]	{	}	
U+0070-007F	√	√	√	√	√	√		Γ		↑	↓	↶	↷	↶	↷	↑	↓

B.4 Latin Modern Math compared to New Computer Modern Math

This example shows the extra symbols available in New Computer Modern Math in comparison to Latin Modern Math as the base font. We use the following setup (including settings for the grayscaled *TUGboat* output, as an example of color overrides):

```
\displayfonttable[hex-digits=head+foot, range-end=1FFFF,
    compare-with=New Computer Modern Math,
    title-format=\caption{Latin Modern Math compared to
        New Computer Modern Math},
    title-format-cont=\caption{LM Math vs.\ NewCM Math,
        \emph{cont.}}},
    compare-color=black, compare-bgcolor=black!5,
    missing-glyph-color=black!50, color=black!75]
{Latin Modern Math}
```

That is, glyphs only in NewCM are shown with a light gray background.

We also extended the range to cover U+10000 to U+1FFFF in order to include the Unicode Math alphabets.

Table 6: Latin Modern Math compared to New Computer Modern Math

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
Basic Latin																
U+0020 - 002F	!	"	#	\$	%	&	'	()	*	+	,	-	.	/	
U+0030 - 003F	0	1	2	3	4	5	6	7	8	9	:	;	<	=	> ?	
U+0040 - 004F	@	A	B	C	D	E	F	G	H	I	J	K	L	M	N O	
U+0050 - 005F	P	Q	R	S	T	U	V	W	X	Y	Z	[\]	^ _	
U+0060 - 006F	`	a	b	c	d	e	f	g	h	i	j	k	l	m	n o	
U+0070 - 007F	p	q	r	s	t	u	v	w	x	y	z	{		}	~ \text{DEL}	
Latin-1 Supplement																
U+00A0 - 00AF	í	€	£	¤	¥	¦	§	„	©	ª	«	¬	®	¬	—	
U+00B0 - 00BF	°	±	²	³	‘	µ	¶	·	¹	º	»	¼	½	¾	¸	
U+00C0 - 00CF	À	Á	Â	Ã	Ä	Å	Æ	Ç	È	É	Ê	Ë	Ì	Í	Î Ï	
U+00D0 - 00DF	Ð	Ñ	Ò	Ó	Ô	Ö	×	Ø	Ù	Ú	Û	Ü	Ý	Þ	ß	
U+00E0 - 00EF	à	á	â	ã	ä	å	æ	ç	è	é	ê	ë	ì	í	î ï	
U+00F0 - 00FF	ð	ñ	ò	ó	ô	ö	÷	ø	ù	ú	û	ü	ý	þ	ÿ	
Latin Extended-A																
U+0100 - 010F	Ā	ā	Ā	ă	Ā	ą	Ć	ć	Ć	ć	Č	č	Đ	đ		
U+0110 - 011F	Ð	đ	Ē	ē	Ē	ě	Ē	ě	Ē	ě	Ĝ	ĝ	Ĝ	ĝ		
U+0120 - 012F	Ğ	ğ	Ğ	ğ	Ğ	ğ	Ĥ	ĥ	Ĥ	ĥ	Ĭ	ĭ	Ĭ	ĭ	Ĭ ı	
U+0130 - 013F	İ	ı	IJ	ij	Ĵ	ј	K	ķ	K	ķ	Ĺ	ĺ	Ĺ	ĺ	Ĺ L	
U+0140 - 014F	Ľ	ľ	Ľ	ň	Ľ	ň	Ľ	ň	Ľ	ň	Ő	ő	Ő	ő	Ő ő	
U+0150 - 015F	Ő	ő	Œ	œ	Ŕ	ŕ	Ŗ	ŗ	Ŗ	ŗ	Ś	ś	Ś	ś	Ś ș	
U+0160 - 016F	Š	š	Ŗ	ŗ	Ŗ	ŗ	Ŗ	ŗ	Ŗ	ŗ	Ӯ	ӻ	Ӯ	ӻ	Ӯ ӻ	
U+0170 - 017F	Ӻ	ӻ	Ӯ	ӻ	Ӯ	ӻ	Ӯ	ӻ	Ӯ	ӻ	Ӯ	ӻ	Ӯ	ӻ	Ӯ ӻ	
Latin Extended-B																
U+0180 - 018F	b	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+01A0 - 01AF	Ø	ø	-	-	-	-	-	-	-	-	-	-	-	-	-	U
U+01B0 - 01BF	ſ	-	-	-	-	-	Z	-	-	-	-	-	-	-	-	-
U+0210 - 021F	-	-	-	-	-	-	-	-	S	s	T	t	-	-	-	-
U+0230 - 023F	-	-	-	-	-	-	-	J	-	-	-	-	-	-	-	-
Spacing Modifier Letters																
U+02C0 - 02CF	-	-	-	-	-	-	^	~	-	-	-	-	-	-	-	-
U+02D0 - 02DF	-	-	-	-	-	-	-	-	◦	·	◦	~	”	-	-	-
Combining Diacritical Marks																
U+0300 - 030F	ˊ	ˊ	ˋ	ˎ	ˎ	˗	˗	˗	˗	˗	˗	˗	˗	˗	˗	˗
U+0310 - 031F	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ
U+0320 - 032F	-	-	-	.	-	-	,	-	-	-	-	-	ˇ	ˇ	ˇ	ˇ
U+0330 - 033F	˘	-	-	=	-	-	-	/	-	-	-	-	-	-	-	˘
U+0340 - 034F	-	-	-	-	-	-	-	-	-	-	-	-	↔	-	-	-
Greek and Coptic																
U+0390 - 039F	-	A	B	Γ	Δ	E	Z	H	Θ	I	K	Λ	M	N	Ξ	Ο
U+03A0 - 03AF	Π	P	-	Σ	T	Υ	Φ	X	Ψ	Ω	-	-	-	-	-	-
U+03B0 - 03BF	-	α	β	γ	δ	ε	ζ	η	θ	ι	κ	λ	μ	ν	ξ	ο
U+03C0 - 03CF	π	ρ	ς	σ	τ	υ	φ	χ	ψ	ω	-	-	-	-	-	-
U+03D0 - 03DF	-	ϑ	-	-	ϕ	ϖ	-	-	-	-	-	-	F	F	-	-
U+03F0 - 03FF	₪	₪	-	-	Θ	€	₪	-	-	-	-	-	-	-	-	-
Latin Extended Additional																
U+1EA0 - 1EAF	À	à	Á	á	Ã	â	À	à	Ã	â	Ã	ã	À	à	Ã	ã
U+1EB0 - 1EBF	Ã	à	Á	á	Ã	â	Ã	à	Ã	à	E	é	È	é	È	é
U+1EC0 - 1ECF	È	è	É	é	Ê	ê	È	è	É	é	I	í	Í	í	Ó	ó
U+1ED0 - 1EDF	Ó	ô	Ò	ò	Õ	õ	Ó	õ	Õ	õ	Ó	ó	Ò	ò	Ò	ò
U+1EE0 - 1EEF	Ó	ð	Ó	ð	Ó	ð	Ó	ð	Ó	ð	Ó	ð	Ó	ð	Ó	ð
U+1EFF - 1EFF	Ù	ȝ	Ù	ȝ	Ù	ȝ	Ù	ȝ	Ù	ȝ	Ù	ȝ	Ù	ȝ	Ù	ȝ
General Punctuation																
U+2000 - 200F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
U+2010 - 201F	-	-	-	-	-	-		-	‘	’	,	,	„	“	„	„
U+2020 - 202F	†	‡	•	►	•	•	-	-	-	-	-	-	-	-
U+2030 - 203F	%	%	'	"	'''	\`	``	~	<	>	※	!!	?	—	—	—
U+2040 - 204F	ؐ	ؑ	ؔ	ؑ	ؔ	ؑ	ؔ	ؑ	ؔ	ؑ	ؔ	ؑ	ؔ	ؑ	ؔ	ؑ
U+2050 - 205F	ؒ	ؓ	ؔ	ؓ	ؔ	ؓ	ؔ	ؓ	ؔ	ؓ	ؔ	ؓ	ؓ	ؓ	ؓ	ؓ
U+2060 - 206F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Currency Symbols																
U+20A0 - 20AF	-	₵	-	-	-	-	-	-	-	-	-	-	€	-	-	-
Combining Diacritical Marks for Symbols																
U+20D0 - 20DF	~	ˇ		ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ	ˇ
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, cont.

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+20E0 - 20EF	-	↔	-	-	△	\		⊓	...	⊟	←	//	-	-	↔	→
U+20F0 - 20FF	*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Letterlike Symbols																
U+2100 - 210F	a%	a/s	©	°C	¢	%	¢u	£	¤	ƒ	g	ℋ	¤	¤	h	ℏ
U+2110 - 211F	ℐ	™	ℒ	ℓ	ℓb	N	Nº	®	®	®	Q	®	®	®	R	®
U+2120 - 212F	SM	TEL	TM	¥	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪
U+2130 - 213F	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪
U+2140 - 214F	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪	₪
Arrows																
U+2190 - 219F	←	↑	→	↓	↔	↑	↗	↘	↙	↔	↗	↖	↗	↖	↖	↑
U+21A0 - 21AF	→	↓	↔	↔	↔	↑	↑	↑	↑	↑	↔	↔	↔	↔	↔	↓
U+21B0 - 21BF	↑	↑	↓	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↑	↑
U+21C0 - 21CF	→	→	↓	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+21D0 - 21DF	↔	↑	⇒	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+21E0 - 21EF	↔	↑	↔	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+21F0 - 21FF	⇒	↖	↘	↖	⇒	↑	↑	↑	↑	↑	↑	↑	↑	↑	↑	↑
Mathematical Operators																
U+2200 - 220F	∨	©	∂	∃	≠	∅	Δ	∇	∈	∉	≡	≠	≡	≡	■	Π
U+2210 - 221F	Π	Σ	-	干	+	/	\	*	◦	•	√	³√	⁴√	∞	∞	Π
U+2220 - 222F	⟨	ʌ	ʌ		ӏ											
U+2230 - 223F	fff	f	f	ƒ	ƒ
U+2240 - 224F	λ	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2250 - 225F	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷
U+2260 - 226F	≠	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡	≡
U+2270 - 227F	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠
U+2280 - 228F	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠	≠
U+2290 - 229F	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□
U+22A0 - 22AF	⊗	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□
U+22B0 - 22BF	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
U+22C0 - 22CF	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ	Λ
U+22D0 - 22DF	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+22E0 - 22EF	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+22F0 - 22FF	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
Miscellaneous Technical																
U+2300 - 230F	∅	⚡	◊	^	∨	¬	¬	¬	{	‘	’	’	’	’	’	’
U+2310 - 231F	—	□	—	□	—	□	—	□	#	#	—	⌚	⌚	⌚	⌚	⌚
U+2320 - 232F	ʃ	ʃ	()	¬	¬	¬	¬	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+2330 - 233F	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+2340 - 234F	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+2350 - 235F	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
U+2360 - 236F	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚	⌚
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+2370 - 237F	𠁠	𠁡	𠁢	𠁣	𠁤	𠁥	𠁦	𠁧	𠁨	𠁩	𠁪	𠁫	𠁬	𠁭	𠁮	𠁯
U+2380 - 238F	𠁰	𠁱	𠁲	𠁳	𠁴	𠁵	𠁶	𠁷	𠁸	𠁹	𠁺	𠁻	𠁼	𠁽	𠁾	𠁿
U+2390 - 239F	𠁾	𠁷	𠁸	𠁹	=	𠁾	𠁿	𠁻	𠁼	𠁽	𠁿	𠁻	𠁼	𠁽	𠁿	𠁿
U+23A0 - 23AF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
U+23B0 - 23BF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
U+23C0 - 23CF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
U+23D0 - 23DF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
U+23E0 - 23EF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
U+23F0 - 23FF	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻	𠁻
Control Pictures																
U+2420 - 242F	-	-	b	□	-	-	-	-	-	-	-	-	-	-	-	-
Box Drawing																
U+2500 - 250F	-	-			-	-			-	-						
U+2510 - 251F	┐	┐	┐	┐	└	└	└	└	┐	┐	┐	┐	┐	┐	┐	┐
U+2520 - 252F	├	├	├	├	┤	┤	┤	┤	├	├	├	├	├	├	├	├
U+2530 - 253F	┬	┬	┬	┬	┴	┴	┴	┴	┬	┬	┬	┬	┬	┬	┬	┬
U+2540 - 254F	+	+	+	+	+	+	+	+	+	+	+	+	+	-	--	-
U+2550 - 255F	=	=	━	━	━	━	━	━	━	━	━	━	━	━	━	━
U+2560 - 256F					─	─	─	─								
U+2570 - 257F	└	/	\	X	-	'	-	-	-	-	-	-	-	-	-	-
Block Elements																
U+2580 - 258F	■	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
U+2590 - 259F	■	▨	▨	▨	▨	-	-	-	-	-	-	-	-	-	-	-
Geometric Shapes																
U+25A0 - 25AF	■	□	○	□	≡	☰	☲	☱	☲	☱	●	○	□	□	□	□
U+25B0 - 25BF	◀	▷	▲	△	▲	△	▶	▷	▶	▷	▼	▷	▽	▼	▼	▽
U+25C0 - 25CF	◀	△	◀	△	◀	△	◆	◇	◆	◇	○	○	○	○	○	●
U+25D0 - 25DF	◐	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑
U+25E0 - 25EF	◐	◑	◀	▶	◀	▶	○	□	□	□	□	□	□	□	□	○
U+25F0 - 25FF	▣	▣	▣	▣	▢	▢	▢	▢	▢	▢	▢	▢	▢	▢	▢	▢
Miscellaneous Shapes																
U+2600 - 260F	★	-	-	-	-	★	★	-	-	○	-	-	-	-	-	-
U+2620 - 262F	-	Ƨ	-	-	-	-	-	-	-	-	-	-	-	-	-	-
U+2630 - 263F	-	-	-	-	-	-	-	-	-	☺	☺	☺	☀	🌙	🌙	-
U+2640 - 264F	♀	-	♂	-	-	-	-	-	-	-	-	-	-	-	-	-
U+2660 - 266F	♠	♥	♦	♣	♠	♥	♦	♦	♣	-	♪	♪	♪	-	♪	♪
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+2670 - 267F	-	-	-	-	-	-	-	-	-	-	-	-	-	⊗	-	-
U+2680 - 268F	□	□	□	□	□	□	□	□	□	□	-	-	-	-	-	-
U+26A0 - 26AF	-	-	-	-	-	♀	-	-	-	-	○	●	○	∞	○○	-
U+26B0 - 26BF	-	-	♀	-	-	-	-	-	-	-	-	-	-	-	-	-
Dingbats																
U+2710 - 271F	-	-	-	-	✓	-	-	-	-	-	-	-	-	-	-	-
U+2720 - 272F	✗	-	-	-	-	-	-	-	-	-	★	-	-	-	-	-
U+2730 - 273F	-	-	-	-	-	*	-	-	-	-	-	*	-	-	-	-
U+2750 - 275F	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
U+2770 - 277F	-	-	()	-	-	-	-	-	-	-	-	-	-	-	-
U+2790 - 279F	-	-	-	-	-	-	-	-	-	-	→	-	-	-	-	-
U+27A0 - 27AF	-	→	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Miscellaneous Mathematical Symbols-A																
U+27C0 - 27CF	↖	△	⊥	⊓	⊔	ℓ	ſ	∨	⊸	⊹	/	⊸	⊵	⊷	⊸	⊷
U+27D0 - 27DF	◊	Δ	Ψ	⊣	⊤	⊖	⊗	⊘	⊙	⊚	⊛	⊕	⊖	⊚	⊕	⊖
U+27E0 - 27EF	◊	◊	◊	◊	□	□	〔	〕	〈	〉	⟨	⟩	〔	〕	()
Supplemental Arrows-A																
U+27F0 - 27FF	↑↑	↓↓	↶	↷	⊕	←	→	↔	⇒	⇒⇒	↔↔	↔	↔	↔	↔	↔
Supplemental Arrows-B																
U+2900 - 290F	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+2910 - 291F	⤠⤠	⤡⤡	⤢⤢	⤣⤣	⤤⤤	⤥⤥	⤦⤦	⤧⤧	⤨⤨	⤩⤩	⤪⤪	⤫⤫	⤬⤬	⤭⤭	⤮⤮	⤯⤯
U+2920 - 292F	⤠⤠⤠	⤡⤡⤡	⤢⤢⤢	⤣⤣⤣	⤤⤤⤤	⤥⤥⤥	⤦⤦⤦	⤧⤧⤧	⤨⤨⤨	⤩⤩⤩	⤪⤪⤪	⤫⤫⤫	⤬⤬⤬	⤭⤭⤭	⤮⤮⤮	⤯⤯⤯
U+2930 - 293F	⤠⤠⤠⤠	⤡⤡⤡⤡	⤢⤢⤢⤢	⤣⤣⤣⤣	⤤⤤⤤⤤	⤥⤥⤥⤥	⤦⤦⤦⤦	⤧⤧⤧⤧	⤨⤨⤨⤨	⤩⤩⤩⤩	⤪⤪⤪⤪	⤫⤫⤫⤫	⤬⤬⤬⤬	⤭⤭⤭⤭	⤮⤮⤮⤮	⤯⤯⤯⤯
U+2940 - 294F	⤠⤠⤠⤠⤠	⤡⤡⤡⤡⤡	⤢⤢⤢⤢⤢	⤣⤣⤣⤣⤣	⤤⤤⤤⤤⤤	⤥⤥⤥⤥⤥	⤦⤦⤦⤦⤦	⤧⤧⤧⤧⤧	⤨⤨⤨⤨⤨	⤩⤩⤩⤩⤩	⤪⤪⤪⤪⤪	⤫⤫⤫⤫⤫	⤬⤬⤬⤬⤬	⤭⤭⤭⤭⤭	⤮⤮⤮⤮⤮	⤯⤯⤯⤯⤯
U+2950 - 295F	⤠⤠⤠⤠⤠⤠	⤡⤡⤡⤡⤡⤡	⤢⤢⤢⤢⤢⤢	⤣⤣⤣⤣⤣⤣	⤤⤤⤤⤤⤤⤤	⤥⤥⤥⤥⤥⤥	⤦⤦⤦⤦⤦⤦	⤧⤧⤧⤧⤧⤧	⤨⤨⤨⤨⤨⤨	⤩⤩⤩⤩⤩⤩	⤪⤪⤪⤪⤪⤪	⤫⤫⤫⤫⤫⤫	⤬⤬⤬⤬⤬⤬	⤭⤭⤭⤭⤭⤭	⤮⤮⤮⤮⤮⤮	⤯⤯⤯⤯⤯⤯
U+2960 - 296F	⤠⤠⤠⤠⤠⤠⤠	⤡⤡⤡⤡⤡⤡⤡	⤢⤢⤢⤢⤢⤢⤢	⤣⤣⤣⤣⤣⤣⤣	⤤⤤⤤⤤⤤⤤⤤	⤥⤥⤥⤥⤥⤥⤥	⤦⤦⤦⤦⤦⤦⤥	⤧⤧⤧⤧⤧⤧⤥	⤨⤨⤨⤨⤨⤨⤥	⤩⤩⤩⤩⤩⤩⤥	⤪⤪⤪⤪⤪⤪⤥	⤫⤫⤫⤫⤫⤫⤥	⤬⤬⤬⤬⤬⤬⤥	⤭⤭⤭⤭⤭⤭⤥	⤮⤮⤮⤮⤮⤮⤥	⤯⤯⤯⤯⤯⤯⤥
U+2970 - 297F	⤠⤠⤠⤠⤠⤠⤠⤠	⤡⤡⤡⤡⤡⤡⤡⤡	⤢⤢⤢⤢⤢⤢⤢⤢	⤣⤣⤣⤣⤣⤣⤣⤣	⤤⤤⤤⤤⤤⤤⤤⤤	⤥⤥⤥⤥⤥⤥⤥⤥	⤦⤦⤦⤦⤦⤦⤥⤥	⤧⤧⤧⤧⤧⤧⤥⤥	⤨⤨⤨⤨⤨⤨⤥⤥	⤩⤩⤩⤩⤩⤩⤥⤥	⤪⤪⤪⤪⤪⤪⤥⤥	⤫⤫⤫⤫⤫⤫⤥⤥	⤬⤬⤬⤬⤬⤬⤥⤥	⤭⤭⤭⤭⤭⤭⤥⤥	⤮⤮⤮⤮⤮⤮⤥⤥	⤯⤯⤯⤯⤯⤯⤥⤥
Miscellaneous Mathematical Symbols-B																
U+2980 - 298F		•	:	{}	}	()	{})	{})	[]	[]	[
U+2990 - 299F]	<	>	↖	↗	↖	↗	↖	↗	↖	↗	↖	↗	↖	↗	↖
U+29A0 - 29AF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+29B0 - 29BF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+29C0 - 29CF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+29D0 - 29DF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+29E0 - 29EF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
U+29F0 - 29FF	⤠	⤡	⤢	⤣	⤤	⤥	⤦	⤧	⤨	⤩	⤪	⤫	⤬	⤭	⤮	⤯
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
Supplemental Mathematical Operators																
U+2A00 - 2A0F	⊕	⊕	⊗	⊕	⊕	□	□	ℳ	ℳ	×	Σ	ℳ	ℳ	ℳ	ℳ	ℳ
U+2A10 - 2A1F	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ
U+2A20 - 2A2F	»	↑	˙	†	˜	‡	‡	‡	‡	‡	‡	‡	‡	‡	‡	‡
U+2A30 - 2A3F	×	×	×	×	×	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗	⊗
U+2A40 - 2A4F	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸
U+2A50 - 2A5F	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸	⊸
U+2A60 - 2A6F	△	△	△	△	△	△	△	△	△	△	△	△	△	△	△	△
U+2A70 - 2A7F	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2A80 - 2A8F	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2A90 - 2A9F	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AA0 - 2AAF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AB0 - 2ABF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AC0 - 2ACF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AD0 - 2ADF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AE0 - 2AEF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
U+2AF0 - 2AFF	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈
Miscellaneous Symbols and Arrows																
U+2B00 - 2B0F	↗	↖	↗	↖	↗	↖	↔	←	↑	↓	↗	↖	↗	↖	↔	↔
U+2B10 - 2B1F	↗	↖	↗	↖	↗	↖	↔	↔	↔	↔	↗	↖	↗	↖	↔	↔
U+2B20 - 2B2F	◇	◇	◇	◇	◇	◇	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
U+2B30 - 2B3F	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2B40 - 2B4F	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2B50 - 2B5F	★	★	★	★	★	★	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
U+2B60 - 2B6F	←	↑	→	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2B70 - 2B7F	←	↑	→	↓	-	-	↖	↗	↙	↘	↔	↔	↔	↔	↔	↔
U+2B80 - 2B8F	↔	↑	↔	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2B90 - 2B9F	↔	↑	↔	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2BA0 - 2BAF	↔	↑	↔	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2BB0 - 2BBF	↔	↑	↔	↓	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔	↔
U+2BC0 - 2BCF	■	◆	●	●	●	●	▲	▼	◀	▶	◐	◑	◑	◑	◑	◑
U+2BD0 - 2BDF	◐	◑	◐	◑	◐	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑
U+2BE0 - 2BEF	◐	◑	◐	◑	◐	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑
U+2BF0 - 2BFF	◐	◑	◐	◑	◐	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑	◑
Supplemental Punctuation																
U+2E10 - 2E1F	-	-	-	-	-	-	-	-	-	-	⌚	-	-	-	-	-

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
CJK Symbols and Punctuation																
U+3010 – 301F	-	-	—	-	-	-	〔	〕	-	-	-	-	-	-	-	-
U+3030 – 303F	~~	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Private Use Area																
U+E000 – E00F	A	B	Γ	Δ	Ε	Ζ	Η	Θ	Ι	Κ	Λ	Μ	Ν	Ξ	Ο	Π
U+E010 – E01F	Ρ	Σ	Τ	Υ	Φ	Χ	Ψ	Ω	α	β	γ	δ	ε	ζ	η	θ
U+E020 – E02F	ι	κ	λ	μ	ν	ξ	ο	π	ρ	ς	σ	τ	υ	φ	χ	ψ
U+E030 – E03F	ω	ε	‡	‡	‡	-	-	-	-	-	-	-	-	-	-	-
U+E040 – E04F	-	A	B	Γ	Δ	E	Z	H	Θ	I	K	L	M	N	Ξ	O
U+E050 – E05F	Π	P	Σ	T	Υ	Φ	X	Ψ	Ω	α	β	γ	δ	ε	ζ	η
U+E060 – E06F	θ	ι	κ	λ	μ	ν	ξ	ο	π	ρ	ς	σ	τ	υ	φ	χ
U+E070 – E07F	ψ	ω	ε	-	-	-	-	-	-	-	-	-	-	-	-	-
U+E370 – E37F	-	-	-	-	-	-	ƒ	ƒ	-	-	-	-	-	-	-	-
U+E390 – E39F	-	-	-	-	-	ƒ	-	ƒ	ƒ	ƒ	ƒ	ƒ	ƒ	-	-	-
U+E3D0 – E3DF	-	-	-	ƒ	-	-	-	-	-	-	-	-	-	-	-	-
U+EA50 – EA5F	-	-	-	-	-	-	ƒ	-	-	-	-	-	-	-	-	-
Alphabetic Presentation Forms																
U+FB00 – FB0F	ff	fi	fl	ffi	ffl	-	-	-	-	-	-	-	-	-	-	-
Arabic Presentation Forms-B																
U+FEF0 – FEFF	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Mathematical Alphanumeric Symbols																
U+1D400 – 1D40F	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
U+1D410 – 1D41F	Q	R	S	T	U	V	W	X	Y	Z	α	β	γ	δ	ε	θ
U+1D420 – 1D42F	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v
U+1D430 – 1D43F	w	x	y	z	A	B	C	D	E	F	G	H	I	J	K	L
U+1D440 – 1D44F	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	a	b
U+1D450 – 1D45F	c	d	e	f	g	-	i	j	k	l	m	n	o	p	q	r
U+1D460 – 1D46F	s	t	u	v	w	x	y	z	A	B	C	D	E	F	G	H
U+1D470 – 1D47F	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X
U+1D480 – 1D48F	Y	Z	a	b	c	d	e	f	g	h	i	j	k	l	m	n
U+1D490 – 1D49F	o	p	q	r	s	t	u	v	w	x	y	z	Α	-	Ϲ	Ͳ
U+1D4A0 – 1D4AF	-	-	g	-	-	j	κ	-	-	Ν	ο	ϙ	-	ſ	τ	ϳ
U+1D4B0 – 1D4BF	υ	ν	ω	χ	γ	ζ	α	β	γ	δ	-	ℓ	-	κ	ι	ϳ
U+1D4C0 – 1D4CF	ϰ	ℓ	μ	ν	-	ρ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ
U+1D4D0 – 1D4DF	Α	Β	Ϲ	Δ	Ε	Ϝ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ	Ϛ
U+1D4E0 – 1D4EF	Ϙ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ	Ϩ
U+1D4F0 – 1D4FF	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ	ϙ
U+1D500 – 1D50F	ϩ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ
U+1D510 – 1D51F	ϩ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ	Ϫ
U+1D520 – 1D52F	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ	ϲ
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+1D530 – 1D53F	ݏ	ݐ	ݑ	ݔ	ݖ	ݦ	ݨ	ݩ	ݪ	ݫ	ݠ	ݢ	ݤ	ݦ	ݧ	ݰ
U+1D540 – 1D54F	ݠ	݂	݃	݄	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	ݎ	ݏ	ݐ
U+1D550 – 1D55F	ݍ	ݎ	ݏ	ݗ	ݘ	ݙ	ݚ	ݛ	ݕ	ݖ	ݗ	ݘ	ݙ	ݚ	ݛ	ݕ
U+1D560 – 1D56F	݊	݋	݃	݄	݅	݆	݇	݈	݉	݊	݋	݃	݄	݅	݆	݇
U+1D570 – 1D57F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D580 – 1D58F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D590 – 1D59F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5A0 – 1D5AF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5B0 – 1D5BF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5C0 – 1D5CF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5D0 – 1D5DF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5E0 – 1D5EF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D5F0 – 1D5FF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D600 – 1D60F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D610 – 1D61F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D620 – 1D62F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D630 – 1D63F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D640 – 1D64F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D650 – 1D65F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D660 – 1D66F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D670 – 1D67F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D680 – 1D68F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D690 – 1D69F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6A0 – 1D6AF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6B0 – 1D6BF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6C0 – 1D6CF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6D0 – 1D6DF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6E0 – 1D6EF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D6F0 – 1D6FF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D700 – 1D70F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D710 – 1D71F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D720 – 1D72F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D730 – 1D73F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D740 – 1D74F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D750 – 1D75F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D760 – 1D76F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D770 – 1D77F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D780 – 1D78F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D790 – 1D79F	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7A0 – 1D7AF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7B0 – 1D7BF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7C0 – 1D7CF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7D0 – 1D7DF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7E0 – 1D7EF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉
U+1D7F0 – 1D7FF	݌	ݍ	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	݅	݆	݇	݈	݉

Arabic Mathematical Alphabetic Symbols

U+1EE00 – 1EE0F	݁	݂	݃	݄	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	ݎ	ݏ	ݐ
U+1EE10 – 1EE1F	݁	݂	݃	݄	݅	݆	݇	݈	݉	݊	݋	݌	ݍ	ݎ	ݏ	ݐ

Table 6: LM Math vs. NewCM Math, *cont.*

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
U+1EE20 – 1EE2F	ۋ	بـ	ـڭ	-	ـە	-	-	ـخـ	-	ـيـ	ـكـ	ـلـ	ـمـ	ـزـ	ـسـ	ـعـ
U+1EE30 – 1EE3F	ـڻـ	ـڻـ	ـڻـ	-	ـڻـ	ـڻـ	ـڻـ	ـڻـ	-	ـڻـ	ـڻـ	ـڻـ	ـڻـ	-	-	-
U+1EE40 – 1EE4F	-	-	ـجـ	-	-	-	-	ـجـ	-	ـيـ	-	ـلـ	-	ـنـ	ـسـ	ـعـ
U+1EE50 – 1EE5F	-	ـقـ	ـصـ	-	ـشـ	-	-	ـخـ	-	ـضـ	-	ـغـ	-	ـبـ	-	ـپـ
U+1EE60 – 1EE6F	-	ـبـ	ـاـ	ـجـ	-	ـهـ	-	ـاـ	ـحـ	ـاـ	ـكـ	ـاـ	ـمـ	-	ـاـ	ـعـ
U+1EE70 – 1EE7F	ـفـ	ـاـ	ـقـ	ـاـ	ـشـ	ـاـ	ـخـ	ـاـ	ـاـ	ـظـ	ـاـ	ـغـ	ـاـ	-	ـاـ	ـپـ
U+1EE80 – 1EE8F	ـهـ	ـبـ	ـجـ	ـهـ	ـهـ	ـهـ	ـهـ	ـهـ	ـهـ	ـيـ	ـهـ	ـلـ	ـمـ	ـنـ	ـهـ	ـعـ
U+1EE90 – 1EE9F	ـفـ	ـصـ	ـفـ	ـلـ	ـتـ	ـئـ	ـخـ	ـهـ	ـظـ	ـضـ	ـغـ	ـظـ	-	-	-	-
U+1EEA0 – 1EEAF	-	ـبـ	ـدـ	ـجـ	ـزـ	ـوـ	ـهـ	ـطـ	ـحـ	ـزـ	ـيـ	ـلـ	ـمـ	ـنـ	ـسـ	ـعـ
U+1EEB0 – 1EEBF	ـفـ	ـصـ	ـفـ	ـرـ	ـقـ	ـصـ	ـتـ	ـشـ	ـخـ	ـذـ	ـظـ	ـضـ	ـغـ	-	-	-
U+1EEF0 – 1EEFF	ـحـ	ـدـ	ـخـ	-	-	-	-	-	-	-	-	-	-	-	-	-

Geometric Shapes Extended

U+1F780 – 1F78F	◀	▲	▶	▼	●	○	○	○	○	○	○	○	○	○	□	□
U+1F790 – 1F79F	□	□	□	□	□	□	□	□	□	●	●	◆	◆	◆	◆	◆
U+1F7A0 – 1F7AF	◊	+	+	+	+	+	+	+	×	×	×	×	×	×	×	★
U+1F7B0 – 1F7BF	★	★	★	★	★	*	*	*	*	*	*	*	*	*	*	*
U+1F7C0 – 1F7CF	▲	▲	▲	▲	+	+	+	+	+	★	★	★	★	★	★	★
U+1F7D0 – 1F7DF	✳	✳	✳	✳	✳	✳	✳	✳	✳	✳	✳	-	-	-	-	-
U+1F7E0 – 1F7EF	●	●	●	●	●	■	■	■	■	■	■	■	■	■	-	-

Supplemental Arrows-C

U+1F800 – 1F80F	←	↑	→	↓	←	↑	→	↓	←	↑	→	↓	-	-	-	-
U+1F810 – 1F81F	←	↑	→	↓	←	↑	→	↓	←	↑	→	↓	←	↑	→	↓
U+1F820 – 1F82F	←	↑	→	↓	←	↑	→	↓	←	↑	→	↓	←	↑	→	↓
U+1F830 – 1F83F	←	↑	→	↓	◀	▲	▶	▼	◀	▲	▶	▼	◀	▲	▶	▼
U+1F840 – 1F84F	◀	♦	♦	▼	◀	♦	♦	▼	-	-	-	-	-	-	-	-
U+1F850 – 1F85F	←	↑	→	↓	↖	↗	↘	↙	↔	↕	-	-	-	-	-	-
U+1F860 – 1F86F	←	↑	→	↓	↖	↗	↘	↙	←	↑	→	↓	↖	↗	↘	↙
U+1F870 – 1F87F	←	↑	→	↓	↖	↗	↘	↙	←	↑	→	↓	↖	↗	↘	↙
U+1F880 – 1F88F	←	↑	→	↓	↖	↗	↘	↙	-	-	-	-	-	-	-	-
U+1F890 – 1F89F	◀	▲	▶	▼	◀	▲	▶	▼	←	↑	→	↓	-	-	-	-
U+1F8A0 – 1F8AF	◀	⇒	◀	⇒	◀	⇒	◀	⇒	◀	⇒	◀	⇒	□	□	-	-
U+1F8B0 – 1F8BF	↗	↘	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Total number of glyphs in Latin Modern Math: 2046

Comparison font New Computer Modern Math has 0 missing and 1958 extra glyphs

B.5 Garamond Libre's Byzantine Musical Symbols

As a final example we exhibit the Byzantine Musical Symbols as provided by Garamond Libre. Command used:

```
\displayfonttable[range-start=1D000, range-end=1D0FF,  
    hex-digits=block,  
    missing-glyph-color=black!50, color=black!75,  
    statistics-format=Total number of glyphs in  
        this block of #1 is #2]  
{Garamond Libre}
```

Note that we have altered the text produced by the statistics, because the default is somewhat misleading if only a portion of the font is displayed. This produces the following table:

Table 7: Garamond Libre

Byzantine Musical Symbols															
U+1D000 - 1D00F	♩	♪	♩	♪	♩	♪	♩	♪	♩	♪	♩	♪	♩	♪	♩
U+1D010 - 1D01F	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫
U+1D020 - 1D02F	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫
U+1D030 - 1D03F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D040 - 1D04F	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫	♫
U+1D050 - 1D05F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D060 - 1D06F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D070 - 1D07F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D080 - 1D08F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D090 - 1D09F	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0A0 - 1D0AF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0B0 - 1D0BF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0C0 - 1D0CF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0D0 - 1D0DF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0E0 - 1D0EF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
U+1D0F0 - 1D0FF	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪	♪
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E

Total number of glyphs in this block of Garamond Libre is 246

- ◊ Frank Mittelbach
Mainz, Germany
<https://www.latex-project.org>
<https://ctan.org/pkg/unicodefonttable>